

W W HENRY CO -- 203 COLD AP ROOF CEMENT -- 8040-00F006767

===== Product Identification =====

Product ID:203 COLD AP ROOF CEMENT

MSDS Date:06/01/1993

FSC:8040

NIIN:00F006767

MSDS Number: BYHQK

=== Responsible Party ===

Company Name:W W HENRY CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-5000

Country:US

Info Phone Num:213-583-4961

Emergency Phone Num:213-583-4961

CAGE:E0927

=== Contractor Identification ===

Company Name:HENRY W W CO

Box:3001

City:LANCASTER

State:PA

ZIP:17604

Country:US

Phone:717-396-2328;717-396-2935

CAGE:11761

Company Name:W W HENRY CO

Address:5608 SOTO ST

City:HUNTINGTON PARK

State:CA

ZIP:90255-5000

Country:US

Phone:213-583-4961

CAGE:E0927

===== Composition/Information on Ingredients =====

Ingred Name:KEROSENE (PETROLEUM), HYDROTREATED (C10-C15 SATURATED
HYDROCARBONS 97%, C10 AROMATICS 3%) *95-4*

CAS:64742-47-8

RTECS #:0A5504000

Fraction by Wt: 20-25%

Other REC Limits:200 PPM EXXON

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: MAY CAUSE IRRITATION OF
NOSE, THROAT & EYES. ASPHYXIATION AT HIGH CONCENTRATION.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:HEADACHE, NAUSEA, GIDDINESS, UNCONSCIOUSNESS,
ASPHYXIATION

===== First Aid Measures =====

First Aid:INHALATION: MOVE TO FRESH AIR. APPLY CPR IF NEEDED. SKIN:
WASH W/SOAP & WATER/WATERLESS CLEANER. EYES: FLUSH W/WATER FOR 15
MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

===== Fire Fighting Measures =====

Flash Point:105F
Lower Limits:1
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION. ABOSRB
W/CLAY, DIATOMACEOUS EARTH/OTHER NONFLAMMABLE ABSORBENT MATERIAL.
LET DRY IN SAFE PLACE.

===== Handling and Storage =====

Handling and Storage Precautions:CLOSE AIR INTAKES ON ROOF DURING
APPLICATION. AVOID HEAT & SOURCES OF IGNITION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE AN ORGANIC RESPIRATOR/AIR SUPPLIED SYSTEM IF
OVER 100 PPM.
Ventilation:REQUIRED TO KEEP VAPORS <100 PPM
Protective Gloves:REQUIRED
Eye Protection:SAFETY GOGGLES
Other Protective Equipment:NONE
Work Hygienic Practices:WASH SKIN W/SOAP & WATER/WATERLESS CLEANER.
DON'T USE SOLVENTS.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:230-400F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:20-25

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:BLACK SMOKE & OXIDES OF CARBON

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE AS SOLID WASTE IN ACCORDANCE W/LOCAL,
STATE & FEDERAL REGULATIONS. COMBUSTIBLE LIQUID UN1992.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.